Theoretical and Applied Fracture Mechanics 12 (1990) 283
Elsevier

AUTHOR INDEX

Volume 12 (1990)

Andreazza, R., see P. Lazzarin (2) 189–193

Bocca, P., Effect of deflection rate on recoverable energy: Unstable crack growth (1) 87–92

Cai, W.M., V. Murti and S. Valliappan, Slope stability analysis using fracture mechanics approach (3) 261–281
Cartwright, D.J., see G. Dowrick (3) 251–260
Chao, C.K., see G.C. Sih (2) 109–119
Chao, C.K., see G.C. Sih (2) 93–108
Chen, X., see Q. Gao (2) 155–160
Chen, Y.Z. and Z.X. Wang, Anti-plane shear of rectangular region with two cracks (3) 225–229
Chou, D.M., see G.C. Sih (1) 19–31
Chow, C.L. and T.J. Lu, A normative representation of stress and strain for continuum damage mechanics (2) 161–187
Cloud, G.L., see S. Dhar (2) 141–147

Dhar, S., G.L. Cloud and S. Paleebut, Measurement of three-dimensional Mode-I stress intensity factor using multiple embedded grid moire technique (2) 141–147
Dowrick, G., D.J. Cartwright and D.P. Rooke, Boundary effects of a reinforced cracked sheet using the boundary element method (3) 251–260

Fellenberg, B., W. Günther and J. Vom Scheidt, Stochastic behavior of a crack with random length and tractions (3) 205–212
Fett, T., Approximative stress intensity factors for Mode-II loading (3) 213–223

Gao, Q. and X. Chen, A fatigue life prediction methodology for cylindrical shell with an inclined crack under torsion (2) 155–160
Gao, Q., see H.W. Liu (3) 195–204
Günther, W., see B. Fellenberg (3) 205–212

Hao, T.-H., Near field behavior in in-plane crack extension in nonlinear incompressible material (3) 241–249
Hong, T.B., see G.C. Sih (2) 109–119
Hsi, W.-H. and K.-Y. Lee, repeated impact response of XT-75 20 mm cannon support (1) 33– 43
Huang, J.S., see K.Y. Lin (1) 73–86

Jeong, D.Y. and O. Orringer, Fatigue crack growth of surface cracks in the rail web (1) 45–58

Lam, Y.C. and K.S. Lian, The effect of residual stress and its redistribution on fatigue crack growth (1) 59–66
Lam, Y.C., A fatigue crack growth model based on the contact stress intensity factor approach (2) 149–154
Lam, Y.C., Mixed mode fatigue crack growth and the strain energy density factor (1) 67–72
Lazzarin, P. and R. Andreazza, Stress distribution in L-shaped butt joint: Welded or bonded (2) 189–193
Lee, K.-Y., see W.-H. Hsi (1) 33–43
Lee, Y.D., see G.C. Sih (1) 1–17
Lian, K.S., see Y.C. Lam (1) 59–66
Lin, K.Y. and J.S. Huang, Analysis of residual stresses in railroad car wheels based on descructive test measurement (1) 73–86
Liu, H.W. and Q. Gao, The equivalence between dislocation pile-ups and cracks (3) 195–204
Lu, T.J., see C.L. Chow (2) 161–187

Murti, V., see W.M. Cai (3) 261–281

Orringer, O., see D.Y. Jeong (1) 45–58

Paleebut, S., see S. Dhar (2) 141–147

Rooke, D.P., see G. Dowrick (3) 251–260

Sih, G.C. and C.K. Chao, Scaling of size/time/temperature - Part 1: Progressive damage in uniaxial tensile spectrum (2) 93–108
Sih, G.C. and C.K. Chao, Scaling of size/time/temperature - Part 2: Progressive damage in uniaxial compressive specimen (2) 109–119
Sih, G.C. and D.M. Chou, Nonequilibrium thermal/mechanical response of 6061 aluminum alloy at elevated temperature (1) 19–31
Sih, G.C. and T.B. Hong, Integrity of edge-debonded patch on cracked panel (2) 121–139
Sih, G.C. and Y.D. Lee, Review of triaxial crack border stress and energy behavior (1) 1–17

Valliappan, S., see W.M. Cai (3) 261–281
Vom Scheidt, J., see B. Fellenberg (3) 205–212

Wang, Z.X., see Y.Z. Chen (3) 225–229

Yang, W., see Z. Zhong (3) 231–240
Yu, S.W., see Z. Zhong (3) 231–240

Zhong, Z., W. Yang and S.W. Yu, Further result on symmetric bending of cracked Reissner plate (3) 231–240